



Water Quality Measurement Solutions

UVT-15

UV Photometer



- Rugged Transportable Case
- Completely Self-Contained
- Simple Calibration Procedures

Accurate %T measurement housed in a rugged, completely self contained case that holds everything needed for measuring the UV %transmission of a sample.

UVT-15 UV Photometer

Specifications

Range:	0 - 100% Transmission
Resolution:	1% Transmission
Accuracy:	± 2%
Principle:	Single beam UV filter photometer with pushbutton 100% transmittance control adjustment
Source:	Low pressure UV Germicidal lamp
Electronics:	Integrated circuit amplification and analog-to-digital conversion
Wavelength Accuracy:	253.7nm
Path Length:	10mm
Response Time:	Full scale deflection in less that 2 seconds
Sample Cell:	10mm x 10mm quartz
Operating Temperature:	0° - 50°C (32° - 122°F)
Power Supply:	Wall Adapter: 120VAC 60Hz 12W UL & CSA approved 220VAC 50Hz 19VA/CE approved
Display:	3½" Digit LCD Display
Dimensions:	11"L x 7"W x5"H
Shipping Dimensions:	11½"L x 11"W x13½"H
Weight:	4 lbs.
Shipping Weight:	6 lbs.

Standard Features

- **Rugged Transportable Carrying Case**
Durability and convenience regardless of sampling location.
- **Completely Self-Contained**
Provides easy access to everything needed to take a measurement.
- **Simple Calibration Procedures**
Calibration initiated with the push of a button ensures accurate readings.
- **Made In The USA**

Ordering Information

Cat. No.	Description
----------	-------------

19573	UVT-15 UV Photometer 120 volt
19574	UVT-15 UV Photometer 240 volt

The UVT-15 UV includes Operating Instruction Decal, Quartz Cuvette and plug in power supply.

Accessories

Cat. No.	Description
----------	-------------

19313	Quartz Cuvette (package of 2)
-------	-------------------------------

 **scientific**
3170 Metro Parkway
Ft. Myers, FL 33916
Phone: (239) 337-2116
Fax: (239) 332-7643
E-mail: hfinfo@watts.com
www.hfscientific.com

Represented by: